

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (rpm)		Weight
	尺寸				额定负荷极限		极限转速		重量
轴承型号	d	D	B	r _{s min}	Dynamic (Cr)	Static (Cor)	Grease	Oil	
					动载	静载	脂	油	Kg
23218	90	160	52.4	2	315	455	1,800	2,800	4.45
23218K	90	160	52.4	2	315	455	1,800	2,800	4.32
23218KW33C3	90	160	52.4	2	315	455	1,800	2,800	4.32
23218W33C3	90	160	52.4	2	315	455	1,800	2,800	4.45
23220	100	180	60.3	2.1	405	580	1,600	2,500	6.47
23220K	100	180	60.3	2.1	405	580	1,600	2,500	6.28
23220KW33C3	100	180	60.3	2.1	405	580	1,600	2,500	6.28
23220W33C3	100	180	60.3	2.1	405	580	1,600	2,500	6.47
23222	110	200	69.8	2.1	515	760	1,400	2,200	9.71
23222K	110	200	69.8	2.1	515	760	1,400	2,200	9.43
23222KW33C3	110	200	69.8	2.1	515	760	1,400	2,200	9.43
23222W33C3	110	200	69.8	2.1	515	760	1,400	2,200	9.71
23224	120	215	76	2.1	585	880	1,300	2,000	12.1
23224K	120	215	76	2.1	585	880	1,300	2,000	11.7
23224KW33C3	120	215	76	2.1	585	880	1,300	2,000	11.7
23224W33C3	120	215	76	2.1	585	880	1,300	2,000	12.1
23226	130	230	80	3	685	1,060	1,200	1,900	14.3
23226K	130	230	80	3	685	1,060	1,200	1,900	13.9
23226KW33C3	130	230	80	3	685	1,060	1,200	1,900	13.9
23226W33C3	130	230	80	3	685	1,060	1,200	1,900	14.3
23228	140	250	88	3	805	1,270	1,100	1,700	18.8
23228K	140	250	88	3	805	1,270	1,100	1,700	18.2
23228KW33C3	140	250	88	3	805	1,270	1,100	1,700	18.2
23228W33C3	140	250	88	3	805	1,270	1,100	1,700	18.8
23230	150	270	96	3	935	1,460	1,000	1,600	24.1
23230K	150	270	96	3	935	1,460	1,000	1,600	23.4
23230KW33C3	150	270	96	3	935	1,460	1,000	1,600	23.4
23230W33C3	150	270	96	3	935	1,460	1,000	1,600	24.1
23232	160	290	104	3	1,050	1,660	960	1,500	30
23232K	160	290	104	3	1,050	1,660	960	1,500	29.1
23232KW33C3	160	290	104	3	1,050	1,660	960	1,500	29.1
23232W33C3	160	290	104	3	1,050	1,660	960	1,500	30
23234	170	310	110	4	1,180	1,960	910	1,400	36.8

23234K	170	310	110	4	1,180	1,960	910	1,400	35.7
23234KW33C3	170	310	110	4	1,180	1,960	910	1,400	35.7
23234W33C3	170	310	110	4	1,180	1,960	910	1,400	36.8
23236	180	320	112	4	1,230	2,000	850	1,300	39
23236K	180	320	112	4	1,230	2,000	850	1,300	37.8
23236KW33C3	180	320	112	4	1,230	2,000	850	1,300	37.8
23236W33C3	180	320	112	4	1,230	2,000	850	1,300	39
23238	190	340	120	4	1,400	2,330	790	1,200	47.6
23238K	190	340	120	4	1,400	2,330	790	1,200	46.2
23238KW33C3	190	340	120	4	1,400	2,330	790	1,200	46.2
23238W33C3	190	340	120	4	1,400	2,330	790	1,200	47.6
23240	200	360	128	4	1,610	2,640	750	1,200	57.2
23240K	200	360	128	4	1,610	2,640	750	1,200	55.5
23240KW33C3	200	360	128	4	1,610	2,640	750	1,200	55.5
23240W33C3	200	360	128	4	1,610	2,640	750	1,200	57.2
23244	220	400	144	4	2,010	3,350	670	1,000	80
23244K	220	400	144	4	2,010	3,350	670	1,000	77.6
23244KW33C3	220	400	144	4	2,010	3,350	670	1,000	77.6
23244W33C3	220	400	144	4	2,010	3,350	670	1,000	80
23248	240	440	160	4	2,430	4,100	610	940	108
23248K	240	440	160	4	2,430	4,100	610	940	105
23248KW33C3	240	440	160	4	2,430	4,100	610	940	105
23248W33C3	240	440	160	4	2,430	4,100	610	940	108
23252	260	480	174	5	2,760	4,700	560	860	141
23252K	260	480	174	5	2,760	4,700	560	860	137
23252KW33C3	260	480	174	5	2,760	4,700	560	860	137
23252W33C3	260	480	174	5	2,760	4,700	560	860	141
23256	280	500	176	5	2,930	5,150	510	790	150
23256K	280	500	176	5	2,930	5,150	510	790	145
23256KW33C3	280	500	176	5	2,930	5,150	510	790	145
23256W33C3	280	500	176	5	2,930	5,150	510	790	150
23260	300	540	192	5	3,450	6,000	470	730	193
23260K	300	540	192	5	3,450	6,000	470	730	187
23260KW33C3	300	540	192	5	3,450	6,000	470	730	187
23260W33C3	300	540	192	5	3,450	6,000	470	730	193